

PRODUCT CATALOGUE

www.timewatchindia.com

CONTENT

01 About Us

02 Our Presence

03 Time Attendance & Access Control

- Fingerprint series
- TrueFace Series
- IRIS series
- Palm & Face series
- AI Based
- Door Access Controller
- Card reader
- Door Lock
- QR Reader/Mini UPS
- UL listed EM lock & Accessories

04 Entrance Security Solutions

- Tripod Turnstiles / Flap barriers
- Swing gates / P-Type Swing Gate
- Full-height Turnstile gates

05 Parking & Traffic Solutions

- Boom Barrier / Toll Barrier
- ANPR System / UHF Reader
- Rising Bollards / Spike Barrier

06 Security Inspection Solutions

- Door Frame Metal Detector
- Handheld Metal Detector / Explosive & Narcotics Detector
- X-Ray Baggage Scanner
- Under Vehicle Surveillance System
- Cargo Scanner

07 Software & Applications

- BioManager Attendance & Payroll
- Payroll Management
- Mobile Application
- iAS Desktop Based
- Visitor Management System
- Canteen Management System
- GYM Management System
- Parking Management System

08 Our Client


About Us

Founded in 2015, TimeWatch Infocom Pvt. Ltd. is a leading manufacturer and solution provider of biometric attendance devices, access control systems, entrance control, parking, and security solutions. We specialize in delivering reliable, Made-in-India technology designed for modern workplaces and secure environments.

With in-house R&D, software development, and manufacturing, TimeWatch offers complete end-to-end solutions, from product design to deployment and support. Our solutions are trusted by corporate enterprises, government organizations, PSUs, healthcare institutions, educational campuses, and industrial facilities.

With a growing presence in India and officially registered operations in the UAE and Saudi Arabia, TimeWatch remains committed to delivering secure, scalable, and future-ready biometric solutions that help organizations stay efficient, compliant, and connected.





Our Presence

TimeWatch Infocom Pvt. Ltd. has a strong and growing presence across India, supported by a wide network of authorized dealers, distributors, and solution partners. Our biometric attendance and security solutions are deployed across major cities, industrial zones, and emerging business regions, enabling reliable and timely customer support.

In addition to India, TimeWatch is officially registered and operational in the UAE, Saudi Arabia, Europe and USA, serving customers across the Middle East with the same commitment to quality, compliance, and service excellence.

With an expanding partner ecosystem and dedicated support teams, we ensure local expertise, efficient service delivery, and seamless project execution for both single-site and large multi-location deployments.



```
JS Targetver.js JS Header.js JS Maps.js JS GuestGrid.js
1 group_info = kmalloc(sizeof(*group_info) + nblocks*sizeof(gid_t *), GFP_USER);
2 if (!group_info)
3     return NULL;
4
5 group_info->ngroups = gidsetsize;
6 group_info->nblocks = nblocks;
7 atomic_set(&group_info->usage, 1);
8
9
10
11 if (gidsetsize <= NGROUPS_SMALL)
12     group_info->blocks[0] = group_info->small_block;
13 else {
14     for (i = 0; i < nblocks; i++) {
15         gid_t *b;
16         b = (void *)__ge
17
18
19
20
```

Problems Output Debug Console Terminal

Live link is activate, You can now view guestbook

Local: <http://localhost:3000>

On your network: <http://192.80.72.55.91:3000>

Development book has not been optimized yet...

In-House Customized Solutions Team

Our In-House Customized Solutions Team offers end-to-end, tailored solutions powered by dedicated R&D, Development, Implementation, Helpdesk, and Support Teams ensuring innovation, seamless execution, fast deployment, and reliable ongoing support for every project.

Time Attendance & Access Control

**QUICK &
ACCURATE
FINGERPRINT
MATCH**



Bio-1



Features

- Identification Mode : Fingerprint, Card, PIN
- User Capacity : 5,000 (Fingerprint, Card,PIN)
- Log Capacity : 1,00,000
- Communication Interface : TCP/IP, USB, Wi-Fi & Hotspot
- Screen Size : 2.4 inch TFT Screen
- Battery : Yes
- Verification Time : <0.5 sec
- Product Dimension : 181.6mm × 135.6mm × 32.7mm

Bio-27



Features

- Identification Mode : Fingerprint, Card, PIN
- User Capacity : 5,000 (Fingerprint, Card,PIN)
- Log Capacity : 1,00,000
- Communication Interface : TCP/IP, USB
- Screen Size : 2.4 inch TFT Screen
- Battery : Yes
- Verification Time : <0.5 sec
- Product Dimension : 181.6mm × 135.6mm × 32.7mm

Bio-20



Features

- Identification Mode : Fingerprint & PIN
- User Capacity : 3,000 (Fingerprint & PIN)
- Log Capacity : 2,00,000
- Communication Interface : USB
- Screen Size : 1.77 inch
- Excel Data Export : Yes
- Verification Time : <0.5 sec
- Product Dimension : 86mm × 86mm × 31.1mm

Bio-4/Bio-4W



Features

- Identification Mode : Fingerprint, Card, PIN
- User Capacity : 10,000 (Fingerprint, Card, PIN)
- Log Capacity : 1,00,000
- Communication Interface : TCP/IP, USB & Wi-Fi
- Screen Size : 2.4 inch
- Verification Time : <1 sec
- Product Dimension : 205mm × 86mm × 30mm

UltraACR801T/802F



Features

- Identification Mode : Finger, Card & PIN
- User Capacity : 5,000 (Finger, Card & PIN)
- Log Capacity : 1,00,000
- Communication Interface : TCP/IP, USB disk, WG26/34, RS-485, RS-232
- Screen Size : 2 inch
- Input : Touch keyboard, T9 input
- Verification Time : <1.08 sec
- Product Dimension : 140mm × 42mm × 18mm

TFP-12E / TFP-12D



Features

- Identification Mode : Fingerprint & Card
- User Capacity : 3,000 (Fingerprint & Card)
- Response Time : 0.1 sec
- Fingerprint Recognition Time : 1.5 sec
- Tamper Alarm : Yes
- Protection : IP65
- Product Dimension : 70.0mm × 70.0mm × 28.0mm

TrueFace1000E/EW



Features

- Identification Mode : Face, Card & PIN
- User Capacity : 1,000 Face & PIN, 3,000 Card
- Log Capacity : 3,00,000
- Communication Interface : TCP/IP, USB, Wi-Fi
- Screen Size : 2.4 inch
- Camera : 2-MP CMOS HD Dual-lens camera
- Verification Time : 0.2 sec
- Product Dimension : 184.9mm × 76.2mm × 20.5mm

TrueFace1000D/DW



Features

- Identification Mode : Face, Finger Card & PIN
- User Capacity : 1,000 Face & PIN, 3,000 Card & Finger
- Log Capacity : 3,00,000
- Communication Interface : TCP/IP, USB, Wi-Fi
- Screen Size : 2.4 inch
- Camera : 2-MP CMOS HD Dual-lens camera
- Verification Time : 0.2 sec
- Product Dimension : 184.9mm × 76.2mm × 20.5mm

TrueFace SERIES



Office



Education



Hospitals



Industrial Sites

TrueFace2000



Features

- Identification Mode : Face, PIN
- User Capacity : 5,000 (Face, PIN)
- Log Capacity : 3,00,000
- Communication Interface : TCP/IP, USB, Wi-Fi, 4G (Optional)
- Screen Size : 4.3 inch
- Camera : 2-MP CMOS HD Dual-lens camera
- Verification Time : <0.2 sec
- Product Dimension : 115mm × 118mm × 27.1mm

TrueFaceT50-IND



Features

- Identification Mode : Face, Card, PIN & QR
- User Capacity : 50,000 (Face, Card, PIN & QR)
- Log Capacity : 3,00,000
- Communication Interface : TCP/IP, USB, Wi-Fi, 4G (Optional)
- Screen Size : 7 inch
- Camera : 2-MP CMOS HD Dual-lens camera
- Verification Time : <0.2 sec

TrueFace3000



Features

- Identification Mode : Face, Card, PIN & QR
- User Capacity : 5,000 (Face, Card, PIN & QR)
- Log Capacity : 3,00,000
- Communication Interface : TCP/IP, USB, Wi-Fi, 4G (Optional)
- Screen Size : 4.3 inch
- Camera : 2-MP CMOS HD Dual-lens camera
- Verification Time : <0.2 sec
- Product Dimension : 115mm × 118mm × 27.1mm

TrueFace3000FP



Features

- Identification Mode : Face, Finger, Card, PIN & QR
- User Capacity : 5,000 (Face, Finger, Card, PIN & QR)
- Log Capacity : 3,00,000
- Communication Interface : TCP/IP, USB, Wi-Fi, 4G (Optional)
- Screen Size : 4.3 inch
- Camera : 2-MP CMOS HD Dual-lens camera
- Verification Time : <0.2 sec
- Product Dimension : 115mm × 118mm × 27.1mm

TrueFace6000



Features

- PoE Support : Yes
- Identification Mode : Face, Card, PIN & QR
- User Capacity : 10,000 (Face, Card, PIN & QR)
- Log Capacity : 3,00,000
- Communication Interface : TCP/IP, USB, Wi-Fi, 4G (Optional)
- Screen Size : 4.3 inch
- Camera : 2-MP CMOS HD Dual-lens camera
- Verification Time : <0.2 sec
- Product Dimension : 180.1mm × 90.1mm × 27.0mm

TrueFace6000FP



Features

- PoE Support : Yes
- Identification Mode : Face, Finger, Card, PIN & QR
- User Capacity : 10,000 (Face, Finger, Card, PIN & QR)
- Log Capacity : 3,00,000
- Communication Interface : TCP/IP, USB, Wi-Fi, 4G (Optional)
- Screen Size : 4.3 inch
- Camera : 2-MP CMOS HD Dual-lens camera
- Verification Time : <0.2 sec
- Product Dimension : 180.1mm × 90.1mm × 27.0mm

TrueFace50



Features

- Identification Mode : Face, Card, PIN & QR
- User Capacity : 50,000 (Face, Card, PIN & QR), 10,000 Fingerprint
- Log Capacity : 3,00,000
- Communication Interface : TCP/IP, USB, 4G (Optional)
- Screen Size : 7 inch
- Camera : 2-MP CMOS HD Dual-lens camera
- Verification Time : <0.2 sec
- Product Dimension : 283.1mm × 130.1mm × 36.0mm

TrueFace50FP



Features

- Identification Mode : Face, Finger, Card, PIN & QR
- User Capacity : 50,000 (Face, Card, PIN & QR), 10,000 Fingerprint
- Log Capacity : 3,00,000
- Communication Interface : TCP/IP, USB, Wi-Fi, 4G (Optional)
- Screen Size : 7 inch
- Camera : 2-MP CMOS HD Dual-lens camera
- Verification Time : <0.2 sec
- Product Dimension : 218mm × 118mm × 24.2mm

ATTENDANCE AND ACCESS DEVICE WITH 1,00,000 USERS



Face, Finger, Card,
PIN & QR Verification



1,00,000 User
Capacity



TCP-IP, Wi-Fi,
USB Connectivity



IP65 Rated
Protection



8 inch
Touch Screen

Model : TrueFace1L/TrueFace1L-FP

IRIS RECOGNITION

Model No.:
TW-IriGoPlus



Iris & Face
Verification

2,00,000
User Capacity

Wi-Fi, Bluetooth
& 4G Connectivity

8 inch
Touch Screen

FACE & PALM RECOGNITION SERIES



Bio-1SE



Features

- Identification Mode : Face, Palm, Fingerprint, Card & PIN
- User Capacity : 1,000 (Face, Palm, Card, PIN) & 3,000 Fingerprint
- Log Capacity : 1,60,000
- Communication Interface : TCP/IP, Wi-Fi, USB, Wiegand & RS485
- Screen Size : 2.8 inch
- Battery : Yes
- Verification Time : <0.6 sec
- Product Dimension : 180mm × 132mm × 33mm

TF-20



Features

- Identification Mode : Face, Palm & PIN
- User Capacity : 3,000 (Face, PIN) & 1,000 Palm
- Log Capacity : 1,60,000
- Communication Interface : USB, Wiegand, RS485
- Screen Size : 1.77 inch
- Excel Data Export : Yes
- Verification Time : <0.6 sec
- Product Dimension : 86mm × 86mm × 23.5mm

ATF-305SE



Features

- Identification Mode : Face, Palm, Fingerprint, Card & PIN
- User Capacity : 3,000 (Face, Finger, Card, PIN) & 1,000 Palm
- Log Capacity : 2,00,000
- Communication Interface : TCP/IP, Wi-Fi, USB, Wiegand & RS485
- Screen Size : 2.4 inch
- Verification Time : <0.6 sec
- Product Dimension : 185mm × 80mm × 29.5mm

TrueFace1LP



Features

- Identification Mode : Face, Palm Card & PIN
- User Capacity : 1,00,000 (Face, Card & PIN) & 10,000 Palm
- Log Capacity : 3,00,000
- Communication Interface : TCP/IP, Wi-Fi, USB, Wiegand, RS-232 & RS-485
- Screen Size : 8 inch
- Verification Time : <0.2 sec
- Product Dimension : 306mm × 133mm × 25mm

AI Based Face Recognition Devie

AIface-T5



Features

- AI Algorithm : Yes
- Identification Mode : Face, Finger, Card & PIN
- User Capacity : 6,000 (Face, Card, PIN) & 12,000 Fingerprint
- Log Capacity : 5,00,000
- Communication Interface : TCP/IP, USB Type-A, WiFi
- Screen Size : 4 inch HD Touch Screen
- Battery : Yes
- Verification Time : ≤0.2 s
- Product Dimension : 151mm × 151mm × 31mm


AI-FaceT7-Pro



Features

- AI Algorithm : Yes
- Identification Mode : Face, Finger, Card & PIN
- User Capacity : 50,000 (Face, Card, PIN) & 10,000 Fingerprint
- Log Capacity : 5,00,000
- Communication Interface : TCP/IP, 4G, Wi-Fi
- Screen Size : 5 inch IPS Touch Screen
- Face Recognition Distance : 0.5m - 2.5m
- Verification Time : <0.2 s

DOOR ACCESS CONTROLLER



TF-1DCW



Features

- Identification Mode : Finger, Card, PIN & Bluetooth
- User Capacity : 5,000 (Card, Bluetooth), 3,000 Finger
- Log Capacity : 3,00,000
- Buzzer: Yes
- Power Supply : 12V DC
- Protection : IK06
- Product Dimension : 186.4 × 185.8 × 58.3mm

TF-2DCW



Features

- Identification Mode : Finger, Card, PIN & QR
- User Capacity : 10,000 Finger & 1,00,000 Card
- Log Capacity : 5,00,000
- Alarm Input & Output : 4 channels, expandable up to 8 with an external alarm module
- Door Status Detection : 2 channels
- Power Supply : Standard PoE; 12 VDC 1A
- Product Dimension : 210mm × 106mm × 34.1mm

TF-4DCW



Features

- Identification Mode : Finger, Card, PIN & QR
- User Capacity : 10,000 Finger & 1,00,000 Card
- Log Capacity : 5,00,000
- Wiegand : 8-channel input
- Door Status Detection : 4 channels
- Anti-pass Back : Yes
- Tamper Alarm : Yes
- Power Supply : AC 100-240 V 1.4 A
- Product Dimension : 397.6 × 262.6 × 82.8 mm

TW-1DC/2DC/4DC



Features

- Capacity : Storage for 42,000 Valid Cards Information and 1,00,000 card swiping Records
- Door control : 1 Nos / 2 Nos / 4 Nos
- Door lock relay : 1 Nos / 2 Nos / 4 Nos
- Quantity of reader interface : 2 Nos / 4 Nos / 8 Nos
- Communication method : TCP/IP
- Voltage input : AC 220V
- Voltage output : 12V

Card Readers

ACR1 / TW-CR12AC



Features

- Identification Mode : Card, PIN
- User Capacity : 1,000 (Card,PIN)
- Cards supported : Proximity
- Read speed : ≤0.2s
- Reading distance : 0-8cm
- Light : Red/Green
- Product Dimension : 117mm × 75mm × 20mm

TW-CR13AC



Features

- Touch Based : Yes
- Identification Mode : Card & PIN
- User Capacity : 1600 (Card & PIN)
- Card supported : Proximity card
- Read speed : <0.1 sec
- Reading distance : 1-5cm
- Product Dimension : 115mm × 75mm × 18mm

TW-CR100ID



Features

- Identification Mode : Card
- Power Supply : 12V DC
- Power Consumption : <2W
- Processor : 8-bit
- Reading Frequency : 125KHz/13.56MHz
- Reading Range : <50mm
- Audio Alert : Beeper
- LED Indicator : Power Indicator, Status Indicator
- IP Rating : IP65

TW-CR100IDIC



Features

- Identification Mode : Card
- Power Supply : 12V DC
- Power Consumption : <500mA
- Processor : 32-bit
- Reading Frequency : 125KHz
- Reading Range : <60mm
- Audio Alert : Beeper
- LED Indicator : Status LED Indicator
- IP Rating : IP64

SMART DOOR LOCK



Face



Finger



Card



PIN



TT App



Bluetooth



TW-SL3000



Features

- **Unlock Options** : Finger, Password, App & Key
- **Capacity** : 300 All
- **Color** : Black
- **Material** : Alloy / Strengthened Glass
- **Lock Cylinder** : Level-C Optional
- **Communication** : Wi-Fi, Bluetooth
- **Life** : ≥6 million times
- **Opening Direction** : Universal
- **Product Dimension** : 296mm x 68mm

TW-N500



Features

- **Identification Mode** : Face, Finger, PIN , App & Key
- **Capacity** : 300 All
- **Color** : Black / Rose Gold
- **Communication** : Wi-Fi
- **Opening Direction** : Universal
- **Battery** : Yes
- **Product Dimension** : 410mm x 72mm

QR Reader / Mini UPS

TW-AER81



Features

- **Identification Mode** : Numeric & Alphanumeric (Optional)
- **Reading Speed** : <200ms
- **Working Volatage** : 5-15V
- **Scanning Range** : 0-20cm
- **Working Temperature** : -20°C ~ 70°C
- **Interface** : Wiegand, RS485, RS232
- **Indicator Light** : Red Working Light, Green feedback light, light green network light

TW12A UPS Adaptor



Features

- **Battery Backup** : Up to 3 hours
- **Input Voltage Range** : AC180-265VAC
- **Cell Charging Cut off** : 4.2V
- **Switching time from Adapter to back up** : <1m Sec
- **Read speed** : <0.1 sec
- **Load in short circuit** : Blue Blinking
- **Low Battery Indication & Fault Battery** : Red Led Glow

MINI UPS
MINI UPS
MINI UPS



Up to 4 Hours
Power Backup



Instant Power
Switchover



Lightweight &
Reliable

Router | CCTV | Biometric | Cordless Phone | POS & IOT Device

EM LOCK & ACCESSORIES

Essential Tools for Secure Entry Control

3 YEAR
WARRANTY
ON UL LISTED
EM LOCK



Smooth Device
Integration

Durable, Long
Lasting Build

Multi-Door
Control Support

TW-280AS



Features

- Holding force : 280KG(600LBS)
- Voltage : DC12V / DC24V Switchable
- Current : 12V/480mA 24V/240mA
- Weight : 2KG
- Dimensions : 250(L)*47(W)*26(H)mm

TW-280BS



Features

- Holding force : 560KG(1200LBS)
- Voltage : DC12V / DC24V Switchable
- Current : 12V/960mA 24V/480mA
- Weight : 4KG
- Dimensions : 500(L)*47(W)*26(H)mm

UL No.: R41142

Accessories



EM Lock 300/600/1200 LBS
With / Without Feedback



EM Lock 1200LBS Dual Leaf
(With Feedback & Without Feedback)



Drop bolt for
Wooden Door / Conceal Fit



Strike Lock



L, U & Z Bracket



No Touch Button




3 x 3 & 1 x 3 Push Button




Emergency Door Release



Thin & Thick Proximity Card



MIFARE Card 1k / 4k



UHF Card / Tag



Power Supply 12V 2/5AMP

ENTRANCE SECURITY SYSTEM

Integration Face, Finger, Card, PIN & QR

25-30 people/min Throughput

Bi-Directional Access

IDEAL FOR



Metro



Airport



Mall



Office



Education

TWLD-TS2700



Features

- Integration : Face, Finger, Card PIN & QR
- Passage Width : 500mm
- Material : SS 304 Stainless steel + Acrylic
- Traffic Direction : Bi-directional
- Traffic Speed : 25-30 People / Min.
- Power : 30-60W
- Life : ≥5 Million times
- Product Dimension : 510(L) x 310(W) x 1010(H)mm

TWLD-TS2715



Features

- Integration : Face, Finger, Card PIN & QR
- Passage Width : 520mm
- Material : SS 304 Stainless steel + Acrylic
- Traffic Direction : Bi-directional
- Traffic Speed : 25-30 People / Min.
- Power : 30-60W
- Life : ≥5 Million times
- Product Dimension : 1200(L) x 220(W) x 980(H)mm

TW-TP-8000HD



Features

- Integration : Face, Finger, Card PIN & QR
- Passage Width : <550mm
- Material : 304 stainless steel
- Traffic Direction : Bi-directional
- Traffic Speed : 25-30 People / Min.
- Power : 30-60W
- Life : 8 Million times
- IP rating : IP54
- Product Dimension : 1400(L) x 250(W) x 1000(H)mm

TW-FB2000/2200



Features

- Integration : Face, Finger, Card PIN & QR
- Passage Width : 550mm
- Material : SUS201, Tempered Glass, Acrylic
- Traffic Direction : Bi-directional
- Traffic Speed : 30-40 People / Min.
- Opening & Closing Speed : 0.5 sec
- Infrared Sensor : 3 Pairs
- Life : ≥6 Million times
- Product Dimension : 1200(L) x 300(W) x 980(H)mm

Swing Gate & P-Type Swing Gate


TWLD-SG2600/2602



Features

- Integration : Face, Finger, Card PIN & QR
- Passage Width : 600mm (950mm Can be customized)
- Material : SUS201, Tempered Glass, Acrylic
- Traffic Direction : Bi-directional
- Traffic Speed : 30-40 People / Min.
- Opening & Closing Speed : 0.6 sec
- Life : ≥6 Million times
- Product Dimension : 1200(L) x 150(W) x 980(H)mm

TWLD-SBG1000



Features

- Integration : Face, Finger, Card PIN & QR
- Passage Width : 562.5mm (900mm Can be Customized)
- Material : SS 304 Stainless steel + Acrylic
- Traffic Direction : Bi-directional
- Traffic Speed : 25-30 People / Min.
- Power : 40-70W
- Life : >8 Million times
- Product Dimension : 250(L) x 200(W) x 980(H)mm

TWLD-SBG2000



Features

- Integration : Face, Finger, Card PIN & QR
- Passage Width : 600mm (900mm for wheelchair)
- Material : 304 stainless steel
- Traffic Direction : Single / Bi-directional
- Working environment : Indoor & outdoor
- Power supply : AC110-220V, 50/60Hz
- Motor type : Brush motor
- Product Dimension : 168mm x 230mm x 1000mm

MAXIMUM SECURITY FOR HIGH-RISK ZONES



**FLEXIBLE ONE-WAY OR
BI-DIRECTIONAL ACCESS CONTROL**



**INTEGRATES WITH MULTIPLE
AUTHENTICATION METHODS: FACE,
FINGERPRINT, CARD, PIN & QR**



**AUTOMATIC RESET AFTER EVERY
PASSAGE**



**HEAVY-DUTY DESIGN FOR
24/7 OPERATION**




FHT2300



Features

- Integration : Face, Finger, Card PIN & QR
- Number of Rod : 3 (FHT2300)
- Passage Width : 550mm
- Material : SS 304 Stainless steel
- Traffic Direction : Bi-directional
- Traffic Speed : Up to 15 People / Min.
- Frequency : 50-60Hz
- Electro magnetic drive : DC
- Arms : 3 spokes@120° angle x10 rotating arms (standard)

FHT2400



Features

- Integration : Face, Finger, Card PIN & QR
- Number of Rod : 4 (FHT2400)
- Passage Width : 550mm
- Material : SS 304 Stainless steel
- Traffic Direction : Bi-directional
- Traffic Speed : Up to 15 People / Min.
- Frequency : 50-60Hz
- Electro magnetic drive : DC
- Arms : 3 spokes@120° angle x10 rotating arms (standard)

FHT2300D



Features

- Integration : Face, Finger, Card PIN & QR
- Number of Rod : 3 (FHT2300D)
- Passage Width : 550mm
- Material : SS 304 Stainless steel
- Traffic Direction : Bi-directional
- Traffic Speed : Up to 15 People / Min.
- Frequency : 50-60Hz
- Electro magnetic drive : DC
- Arms : 3 spokes@120° angle x10 rotating arms (standard)

FHT2400D



Features

- Integration : Face, Finger, Card PIN & QR
- Number of Rod : 4 (FHT2400D)
- Passage Width : 550mm
- Material : SS 304 Stainless steel
- Traffic Direction : Bi-directional
- Traffic Speed : Up to 15 People / Min.
- Frequency : 50-60Hz
- Electro magnetic drive : DC
- Arms : 3 spokes@120° angle x10 rotating arms (standard)

PARKING & TRAFFIC SOLUTIONS

- Automated Vehicle Entry & Exit Control
- ANPR & UHF RFID Enabled
- High-Security Bollards & Tyre Killers
- Smart, Scalable & Low Maintenance Design



TW-DCLD-7000



Features

- Boom Length : Straight Arm-6m, Folding Arm-4.5m
- Lifting Speed : 1.5 - 6s
- Power Supply : 220V ± 10% 50 - 60Hz
- Voltage : AC110V/220V
- Remote Control Distance : <30m
- Duty Cycle : 5 Million
- Box Thickness : Full-thickness of 1.5mm
- Product Dimension : 320mm x 250mm x 940mm

TW-DCLD-8000



Features

- Boom Length : Max 6m
- Lifting Speed : 0.6 - 6s
- Power Supply : AC110-220V, 50/60Hz
- Voltage : DC24V
- Remote Control Distance : <100m
- Waterproof Grade : IP54
- Integration : IC/ID card reader, QR Code scanner, Traffic Light, Loop detector, Radar sensor
- Product Dimension : 350mm x 235mm x 1000mm

ANPR & UHF Reader

TW-LPR2000



Features

- Resolution : 4mp / 8mp
- IR Range : 20m
- Lens : 12mm
- Sensor : Sony
- Compression : H.264
- Frame Rate : 30fps
- Records Capacity : 1,00,000 records
- Flash Memory : 32-128gb
- Wi-Fi : 2.4GHz & 5.0GHz, IEEE 802.11g Wireless

TW-UR12/12-UR5/5T



Features

- Working Frequency : National Standard (920-925MHz), American Standard (902-928MHz), Or customize other Frequency
- Support Protocol : ISO18000-6B, ISO18000-6C (EPC GEN2)
- Frequency Power : 0-26dBm, adjustable via software
- Reading Sensitivity : 1-5M (TW-UR5/5T) 1-15M (TW-UR12/12T)
- Reading Speed : Dual polarization reading
- Working Status Indication : Buzzer

Hydraulic Bollard & Spike Barrier

TW5200



Features

- **K4 CRASH RATED CERTIFIED BOLLARD**
- Control system : Electric hydraulic
- Power supply : 220V
- System power : 300W
- Weight capacity : >100 tons of Container Trucks
- Opening time : 1.5-3 Sec (can be adjustable)
- Closing time : 1.5-3 Sec (can be adjustable)
- Controller Support : 8 Bollard
- Blade height : 600mm

TW5500



Features

- Control system : Electric
- Power supply : 220V
- System power : 500W
- Weight capacity : 100 tons
- Opening time : 1-3 Sec (can be adjustable)
- Closing time : 1-3 Sec (can be adjustable)
- Remote control distance : >100m
- Blade height : 128 + 5mm



SECURITY INSPECTION SOLUTIONS

TW100SE (Single Zone DFMD)



Features

- Power Supply : AC90V-240V 50/60Hz
- Power Consumption : 12W
- People Counting : Yes
- Through Put Rate : 30
- Battery Backup : Optional
- Indicator Light : Two LED Red & Green
- Operating Frequency Range : 1-50 Bands
- Password protection : Yes
- Volume adjustable mode : Yes

TWD-2101 (6/9/12 Zone DFMD)



Features

- Detection Zones : 6/9/12 Zone
- Sensitivity : 1000 levels
- Control Panel : 7 inch LCD Screen
- People Counting : Yes
- Throughput Rate : 30-40 people/min
- Battery Backup : Optional
- Alarm Indicator : LED light and sound
- Power : AC100-240V-50/60Hz
- Working Voltage : DC 12V/3A
- Camera : Optional

TWD-2618 (18 Zone DFMD)



Features

- Detection Zones : 18 Zone
- Sensitivity : 1000 levels
- Control Panel : 7 inch LCD Screen
- People Counting : Yes
- Throughput Rate : 30-40 people/min
- Battery Backup : Optional
- Alarm Indicator : LED light and sound
- Power : AC100-240V-50/60Hz
- Working Voltage : DC 12V/3A
- Camera : Optional

TWD-2333 (33 Zone DFMD)



Features

- Detection Zones : 33 Zone
- Sensitivity : 1000 levels
- Control Panel : 7 inch LCD Screen
- People Counting : Yes
- Throughput Rate : 30-40 people/min
- Battery Backup : Optional
- Alarm Indicator : LED light and sound
- Power : AC100-240V-50/60Hz
- Working Voltage : DC 12V/3A
- Camera : Optional

HHMD & Narcotics Detector

TW-HH100



Features

- Net Weight : 170g (No battery)
- Operation Voltage : DC 7-12V
- Staple : 30-50mm
- Tiananmen-Style Pistol : Vertical : 1.6mm, Horizontal : 1.6mm
- 38 Caliber Pistol : 250mm
- Battery : Optional
- Audible or Vibrating Alarm : Yes
- Product Dimension : 295 x 68 x 28mm

TWND-800



Features

- Frequency range : 2.404 GHz - 2.472 GHz
- Receiving sensitivity : <125dBm
- Battery working time : 4.0H
- Battery type : Replaceable lithium battery
- Detection distance : >6M, C-class product

TW-NE2000



Features

- Principle : Ion mobility spectrometry
- Ionizer : Non-radioactive ionization source
- Sensitivity : Nanogram (10-9-10-7gram)
- Analyzing time : 8 seconds
- Warm up time : <20 minutes
- Display Screen : 7 inches touch screen
- Battery Life : >3 hours
- Device interface : USB, LAN, HDMI
- Narcotics : Cocaine, Heroin, Morphine, THC, Methamphetamine(MA), Ketamine Fentanyl etc.
- Explosives : TNT, RDX, BP, PETN, NG, AN, HMTD, Tetryl, TATP etc.

TW-NE3000



Features

- Analysis time : <5s
- Start-up time : <10s
- Detection Sensitivity : Particulate: TNT LOD <0.05ng Vapor: PPM
- False alarm rate : <1%
- Display Screen : 3" TFT Color display Screen
- Battery : Two Li-ion Rechargeable Battery
- Battery Working Time : Up to 8 hours
- Protection Level : IP53
- Substances detected : TNT, DNT, MNT, Picric Acid, RDX, PETN, TATP, NG, Tetryl, HMX, C4, NA, AN, Black Powder, etc.

X-RAY BAGGAGE SCANNER



AI Enable



HD Color Display



Compact Design



Energy Saving



Baggage Counter



IDEAL FOR



Metro



Airport



Mall



Office



School

TW5030



Features

- Tunnel Size : 50cm x 30cm
- X-Ray tube Anode Voltage : 80 Kv
- Penetration Steel : 12mm
- Conveyor Speed : 0.2 m/s
- Baggage Counter : Yes
- Maximum Belt Load : 80 kg
- Power Supply : 220-240 VAC
- Product Dimension : 1660 mm × 746 mm × 1165 mm

TW5030 (AI)



Features

- AI Enabled (Auto Detects the object) : Yes
- Tunnel Size : 50cm x 30cm
- X-Ray tube Anode Voltage : 80 Kv
- Penetration Steel : 8mm
- Conveyor Speed : 0.2 m/s
- Baggage Counter : Yes
- Maximum Belt Load : 80 kg
- Power Supply : AC 110V to 230V
- Product Dimension : 1483(L) × 730(W) × 1060(H)

TW6040B



Features

- Tunnel Size : 60cm x 40cm
- X-Ray tube Anode Voltage : 160 Kv
- Penetration Steel : 30mm
- Conveyor Speed : 0.2 m/s
- Baggage Counter : Yes
- Maximum Belt Load : 170kg
- Power Supply : AC 220V - 240V, 50/60Hz
- Product Dimension : 2648 × 844 × 1206mm

TW6040B (AI)



Features

- AI Enabled (Auto Detects the object) : Yes
- Tunnel Size : 60cm x 40cm
- X-Ray tube Anode Voltage : 160 Kv
- Penetration Steel : 30-35 mm
- Conveyor Speed : 0.2 m/s
- Baggage Counter : Yes
- Maximum Belt Load : 165 kg
- Power Supply : AC 220V - 240V, 50/60Hz
- Product Dimension : 2011(L) × 887(W) × 1260(H)

TW6550



Features

- Tunnel Size : 65cm x 50cm
- X-Ray tube Anode Voltage : 160 Kv
- Penetration Steel : 30-35 mm
- Conveyor Speed : 0.2 m/s
- Baggage Counter : Yes
- Maximum Belt Load : 160kg
- Power Supply : AC 220V - 240V, 50/60Hz
- Product Dimension : 2194 x 902 x 1362,5mm


Ai-Scan-DV



Features

- AI Enabled (Auto Detects the object) : Yes
- Tunnel Size : 60cm x 40cm
- X-Ray tube Anode Voltage : 160 Kv
- Penetration Steel : 30-35 mm
- Conveyor Speed : 0.2 m/s
- Conveyor Height : 600mm
- Baggage Counter : Yes
- Maximum Belt Load : 180 kg
- Power Supply : AC 220V, 50Hz/60Hz
- Product Dimension : 2311(L) × 1172(W) × 1260(H)

TW100100



Features

- Tunnel Size : 100cm x 100cm
- X-Ray tube Anode Voltage : 160 Kv
- Penetration Steel : 35mm (±2mm)
- Conveyor Speed : 0.2 m/s
- Baggage Counter : Yes
- Maximum Belt Load : 180-200 kg
- Power Supply : AC 220V - 240V, 50/60Hz
- Product Dimension : 3638 x 1295 x 1916,5mm

TW100100(AI)



Features

- AI Enabled (Auto Detects the object) : Yes
- Tunnel Size : 100cm x 100cm
- X-Ray tube Anode Voltage : 160 Kv
- Penetration Steel : 30-35 mm
- Conveyor Speed : 0.2 m/s
- Baggage Counter : Yes
- Maximum Belt Load : 200kg
- Power Supply : AC220V+10%--15% 50±3Hz
- Product Dimension : 3592 (L) x 1360(W) x 1894(H)mm


TW3000



Features

- Scanning rate : 18kHz
- Vehicle speed : 1-60 km/h
- View angle : 170 degrees
- Lighting : 160W
- Load-bearing weight : 30T
- Waterproof grade : IP68 (the highest level)
- Imaging speed : <1 second
- Product Dimension : 450 x 400 x 88 mm

TW3300



Features

- Scanning rate : 18kHz
- Vehicle speed : 1-60 km/h
- View angle : 170 degrees
- Lighting : 160W
- Load-bearing weight : 50T
- Waterproof grade : IP68 (the highest level)
- Imaging speed : <1 second
- Product Dimension : 1200 x 350 x 210mm

Cargo Scanner

CARGO SCANNER

 3 x 3 meter
Tunnel Size

 AI Threat
Detection

 Dual/Multi view
Scanning

 Large Cargo
Support

 High-Penetration
Imaging






SOFTWARE & APPLICATIONS

BIOMANAGER

SMART ATTENDANCE & PAYROLL MANAGEMENT

ONE PLATFORM. ONE DATA. ALL DEVICES.



Web Dashboard & Cloud Access



Real-Time Sync Across Platforms

ATTENDANCE & WORKFORCE TRACKING

Employee Enrollment from Mobile App

Face Verification & Photo Attendance

Real-Time GPS Location Capture

MOBILE WORKFORCE MANAGEMENT

Attendance from Mobile

Photo, GPS, Geo-Fencing & Route Tracking

Leave & Out-Duty Requests

HR, LEAVE & REPORTS

Multi-Level Leave Approval

Email & App Notifications

Daily Headcount & MIS Reports



PAYROLL MANAGEMENT

Seamless
multi-currency
payroll management
across all locations



Multi-Currency
Payroll Processing

Overtime, Leave
& Holiday
Payroll Integration

Tax, Loan &
Advance Management


Monthly & Daily
Wage Payroll
Processing

Automated Salary
Calculation

Salary Slips
Generation
(PDF & Email)

Secure Payroll
Reports & Audit Logs

Employee Wise
Payroll Management



Live Face Verification



MOBILE APPLICATION

Live Attendance Monitoring

Cloud-Connected for Anytime Access

Daily head count on Dashboard.

Geo-Fencing enabled for on-field staff


View check-in location & time

Mobile Enrollment.

“ SCAN HERE TO DOWNLOAD THE MOBILE APP ”



iAS DESKTOP BASED TIME ATTENDANCE SOFTWARE



Shift Roster for
Multiple Shifts

Automated Salary
Calculation

Basic Payroll
Management

Office Time Policy
Configuration

Leave Management
System

Device Management &
Monitoring

Monthly & Daily
Attendance Reports

Employee-wise Payroll
Management



VISITOR MANAGEMENT SYSTEM



Pre-Appointments & Host Notifications



Real-Time Visitor Tracking



ID & Badge Management



Enhanced Security & Compliance



CANTEEN MANAGEMENT SYSTEM


**Streamline food distribution
with smart automation**

**BIOMETRIC & CARD
BASED ACCESS**

**EXPORT DATA TO PAYROLL
AND BILLING SOFTWARE**

**MEAL & ITEM WISE
CONTROL**

**INTEGRATION WITH
PRINTER**



GYM MANAGEMENT

User Friendly software to manage large no. of Members

Automatic mail alert for members regarding payment

Track member workout Timing (in & out)

Comprehensive software From member Registration to settlements

Validity set option along with reports on collections

Other functions include billing, Scheduling, Training & Tracking




PARKING MANAGEMENT SYSTEM

ANPR-based parking system that allows entry only for authorized vehicles.


RFID-based parking management ideal for restricted areas with authorized vehicle access only.

Automatic boom barrier with RFID and ANPR allows access only to authorized vehicles.



Our Clients

TimeWatch is trusted by government bodies, PSUs, enterprises, and private organizations. Our biometric, security, and automation solutions deliver reliable, compliant, and high-performance systems across diverse industries and critical infrastructures.





Thank You

Towards a World of trust, Safety & Security

-  **H.O:** D-162, Okhla Industrial Area, Phase-1, Delhi 110020
-  **Email:** sales@timewatchindia.com
-  **Phone:** 011 4191 6615
-  **Mobile:** +91 95999 53923
-  **Website:** www.timewatchindia.com